

EAN : 542503 853124 4

SKU : SXAE00025

- Charge & maintenance functions
- Automatic management by microprocessor
- Maximum current 4 Amp
- Suitable for 6V / 12V batteries
- Up to 8 steps intelligent charging cycles
- No battery removal required
- For all types of lead-acid batteries
- Supplied with clamps and eyelets



SPECIFICATIONS

INPUT	Voltage	220 - 240 Volt AC 50 - 60Hz	
	Plug	EU	Type Standard
OUTPUT	Nominal Voltage	6V - 12V	
	Cable length	1,5m + 0,5m clamps cable and O-rings cable	
	Terminals	Clamps and O-rings	
CAPACITY	Charge	4 - 80 Ah	Maintain 4 - 120 Ah
	Recovery	YES	
	Compatibility	Lead Acid battery : AGM , GEL, VLRA, WET, LIQUID	
INTERFACE	LCD Display	Charging status - Error Indicator	
	MMI	3 selections: voltage - slow/fast - battery type (STD/AGM)	
IP CLASSIFICATION	IP 65		
CERTIFICATION	CE EN60335 - 2 - 29 - LVD - EMC - RoHS		

SKU	EAN code	5425038 53124 4			
	Length	165mm	Width	55mm	Height 280mm
	Gross weight	860gr	Net weight	630gr	
Carton box	EAN code	2 5425038 53124 8			
	Length	577mm	Width	198mm	Height 185mm
	Gross weight	5,20kg	Net weight	3,78kg	
	Qty of SKUs per carton box	6			
PALLET	EAN code	4 5425038 53124 2			
	Length	120cm	Width	80cm	Height 145cm
	Gross weight	322kg	Net weight	212kg	
	Carton per layer	8	Qty of layers	7	Cartons per pallet 56
	Qty SKUs per pallet	336			
	type of pallet	Plywood pallet			